

# ECOLOFENCE 36/11

## Silt Fencing

ECOLOFENCE 36/11 is a pre-assembled sediment control fence made exclusively by **Price and Company, Inc.** From our select wood stock to the certified *Skaps Industries* geotextile, it meets rigorous physical, mechanical and hydraulic performance characteristics. This attention to quality translates to better value for our customers. Our fences are virtually problem-free during installation and provide long-term protection against sediment runoff. When you want to safeguard your site from becoming a sediment source, use **ECOLOFENCE 36/11**.



| FENCE CHARACTERISTICS |                               |
|-----------------------|-------------------------------|
| Fence Length          | 100'                          |
| Geotextile Width      | 36"                           |
| Geotextile Type       | Skaps W100                    |
| Post Composition      | No. 2 Common Hardwood         |
| Post Length           | 42"                           |
| Post Cross-Section    | 1.25" x 1.25"                 |
| Post Spacing          | 10'                           |
| Post Point            | Rotary                        |
| Lath Composition      | No. 2 Common Hardwood         |
| Lath Dimensions       | 1.125" x 0.437" x 30"         |
| Fence Assembly        | 5 - 16 ga. Galvanized Staples |



| SKAPS W100 GEOTEXTILE CHARACTERISTICS |             |                     |        |
|---------------------------------------|-------------|---------------------|--------|
| Property                              | Test Method | Units               | MARV   |
| Grab Tensile                          | ASTM D-4632 | lbs                 | 124    |
| Grab Elongation                       | ASTM D-4632 | %                   | 15     |
| Trap Tear                             | ASTM D-4533 | lbs                 | 45     |
| Puncture                              | ASTM D-4833 | lbs                 | 65     |
| Mullen Burst                          | ASTM D-3786 | psi                 | 300    |
| Permittivity                          | ASTM D-4491 | sec <sup>-1</sup>   | 0.1    |
| Water Flow                            | ASTM D-4491 | gpm/ft <sup>2</sup> | 10     |
| AOS                                   | ASTM D-4751 | U.S. Std            | 30     |
| UV Resistance                         | ASTM D-4355 | %/hrs               | 70/500 |

The information presented herein is, to the best of our knowledge, true and accurate. No warranty or guarantee, expressed or implied, is made regarding the performance of any product, since the manner of use and handling are beyond the control of Price and Company, Inc. Nothing contained herein is to be construed as permission or as a recommendation to infringe on a patent.

