

ECOLOFENCE MDOT

Silt Fencing

ECOLOFENCE MDOT is a pre-assembled sediment control fence made exclusively by **Price and Company, Inc.** From our select wood stock to the certified *Skaps Industries* geotextile, it meets rigorous physical, mechanical and hydraulic performance characteristics. This attention to quality translates to better value for our customers. Our fences are virtually problem-free during installation and provide long-term protection against sediment runoff. When you want to safeguard your site from becoming a sediment source, use **ECOLOFENCE MDOT**.



FENCE CHARACTERISTICS	
Fence Length	100'
Geotextile Width	36"
Geotextile Type	Skaps W100
Post Composition	No. 2 Common Hardwood
Post Length	42"
Post Cross-Section	1.5" x 1.5"
Post Spacing	6.5'
Post Point	Rotary
Lath Composition	No. 2 Common Hardwood
Lath Dimensions	1.125" x 0.437" x 30"
Fence Assembly	5 - 16 ga. Galvanized Staples



ECOLOFENCE MDOT meets *MDOT* specifications and is listed on the Approved Products list, Materials Sampling Guide

SKAPS W100 GEOTEXTILE CHARACTERISTICS			
Property	Test Method	Units	MARV
Grab Tensile	ASTM D-4632	lbs	124
Grab Elongation	ASTM D-4632	%	15
Trap Tear	ASTM D-4533	lbs	45
Puncture	ASTM D-4833	lbs	65
Mullen Burst	ASTM D-3786	psi	300
Permittivity	ASTM D-4491	sec ⁻¹	0.1
Water Flow	ASTM D-4491	gpm/ft ²	10
AOS	ASTM D-4751	U.S. Std	30
UV Resistance	ASTM D-4355	%/hrs	70/500

The information presented herein is, to the best of our knowledge, true and accurate. No warranty or guarantee, expressed or implied, is made regarding the performance of any product, since the manner of use and handling are beyond the control of Price and Company, Inc. Nothing contained herein is to be construed as permission or as a recommendation to infringe on a patent.

