

Geopro® Wood Plus

Hydraulic Mulch Product Data Sheet

Geopro Wood Plus is a pre-blended mix of wood fiber and polymer binder which is hydraulically applied to exposed soil surfaces to assist in the control of both erosion and sediment transport as well as improve the microenvironment for seed germination and early plant growth.

Components:

Wood ¹	100 ±%
Silt Stop® binder ²	0.3 ±%

¹ Moisture content	12 ±3%
pH @ 25 degrees C	6.5 ±1
Water holding capacity	1.6 gal/lb
Toxicity	Non-toxic

² Other *Silt Stop* soil binders may be custom ordered
Listed - MDEQ Water Treatment Additive List
EPA toxicity tested - acute and chronic testing. Toxicity report & MSD sheet available.

Packaging: 40 lbs bales

Preparation: **Geopro Wood Plus** is added to the hydraulic mulching equipment after the tank is at least 50% water filled and with agitation in progress. No more than 50 lbs of **Geopro Wood Plus** should be added for each 100 gallons of water. Continue mixing for at least 5 minutes after **Geopro Wood Plus** has been added, ensuring complete wetting of all components prior to application. Additional *Silt Stop* can be used to increase mulch/seed/fertilizer/amendment/soil stabilization [contact your *Price and Company* **Regional Representative** for additional information].

Application: **Geopro Wood Plus** should be applied in one or more layers to ensure complete and even coverage of all exposed soil surfaces. A suggested minimum application rate for assistance in reducing erosion and sedimentation is 2000 lbs per acre.

Geopro is a trademark registered to Price and Company, Inc.
Silt Stop is a trademark registered to Applied Polymer Systems, Inc.

